











# Spoon Chair

Antonio Citterio with Toan Nguyen

A monoshell light office chair on castors, Spoon Chair is the result of a totally avant-garde production process. The innovative dual-component injection moulding technology used to produce this chair creates a “layered” product. Two different thermoplastics are moulded at the same time, one for beauty (exterior) and the other for its high mechanical resistance, giving Spoon Chair its highly technological characteristics and maximum flexibility which comes from its highly customisable thickness which adapts to the user’s weight. The easy-to-use handle regulating the mechanism is concealed inside trunk of the bottom shell to avoid interrupting its sinuous line. Ideal for offices, there is also a fireproof version of the Spoon Chair.



## 4819/6819

Mat	structure	cushion
02/orange-orange		
03/white-black		
04/blue-blue		
07/grey-black		
09/black-black		

## Material

Batch-dyed polypropylene

	reached level
EN 1022:2005	positive
6.2.1	(maximum level) 5
6.2.2	(maximum level) 5
6.6	(maximum level) 5
6.7	(maximum level) 5
6.8	(maximum level) 5
6.10	(maximum level) 5
6.12	(maximum level) 5
6.13	(maximum level) 5
6.15	(maximum level) 5
6.16	(maximum level) 5
6.17	(maximum level) 5

**4819**



**6819**

fire tested version\*\*

chair width	height	seat height	diameter base	arms height	weight kg.
-------------	--------	-------------	---------------	-------------	------------

60	83,5÷92,5	45÷54	70	68,5÷77,5	12,000
----	-----------	-------	----	-----------	--------

60	83,5÷92,5	45÷54	70	68,5÷77,5	12,000
----	-----------	-------	----	-----------	--------

\*\* IT Standard UNI 9175 Positive Catas and CSI fire test. Ministerial certification in progress

UK Standard BS 5852 CRIB 5, BS7176 and EN 1021

US CALIFORNIA Standard TB 117

packaging

quantity	weight kg.	volume m <sup>3</sup>
----------	------------	-----------------------

**4819**

1	16,800	0,450
---	--------	-------

**6819**

1	16,800	0,450
---	--------	-------